

See chart below for all wire specifications.



### BRASS WIRE

**Cat. No. 4501** - 16 ga.  
Brass, 32 ft. roll (9.75m)

**Cat. No. 45001** - 20 ga.  
Brass, 79 ft. roll (24m)



### TINNED COPPER WIRE

**Cat. No. 4520** - \_\_\_  
4 oz. (113g) spool.

**Cat. No. 4521** - \_\_\_  
1 lb. (454g) spool.  
Bright silver. Solders easily to lead, foil or zinc. Soft temper for easy forming.



### BRAIDED TINNED COPPER WIRE

**Cat. No. 4525**  
100 ft. (30m) roll.  
1/8" (3mm) wide, approximately .020" (5mm) thick. Excellent for borders and trim. Solders well.



### HIGH TEMP WIRE

**Cat. No. 450417**  
10 ft. (3m) roll.  
.045" (1.1mm) diameter, 17 ga. wire. General purpose wire. Remains strong in extreme heat from kiln firings and withstands high temperatures for long periods.



### HIGH TEMP STAMEN WIRE

**Cat. No. 450424**  
10 ft. (3m) long, .020" (0.5mm) diam., 24 ga. wire.



### COPPER WIRE

**Cat. No. 4502** -  
1 lb. (454g) spool.

**Cat. No. 4503** -  
4 oz. (113g) spool.  
Pure copper wire for fusing projects. Solders well to lead, zinc or copper foil.



### TWISTED TINNED COPPER WIRE

**Cat. No. 45261** - 25 ft. roll (20 ga).  
**Cat. No. 45262** - 100 ft. roll (20 ga).  
**Cat. No. 45263** - 25 ft. roll (14 ga).  
**Cat. No. 45264** - 100 ft. roll (14 ga).  
Tightly twisted pair of tinned copper wire in two gauge sizes and two convenient spool lengths.



### TWISTED SQUARE BRIGHT BRASS WIRE

**Cat. No. 45280**  
24 ft. Double strand twisted wire. 20 ga.



### HANDI-BENDER

**Cat. No. 24555**

Handi-Bender is a rugged cast aluminum bending jig for use on a board, bench or in a vise. It has three steel bending pins. Includes instructions for making basic bends such as centered and off-centered eyes, curves, angles, circles and spirals. Instructions also cover wire straightening, soldering and wire cutting. Diagrams of shapes that can be made with the Handi-Bender are included.



### WIRE FORMING PEGBOARD

**Cat. No. 24556**  
A rugged cast aluminum bending pegboard with 16 steel bending pins.

Includes instructions for making basic bends such as centered and off-centered eyes, curves, angles, circles and spirals. Instructions also cover wire straightening, soldering and wire cutting.

### WIRE SPECIFICATIONS

Cat. No.	Description	Dimensions*			Weight*		Pkg.	Length	
		Ga.	Std.	Metric	Standard	Metric		Std.	Metric
4502-14	Pure Copper	14	.064"	1.6mm	1 lb.	454g	Spool	80 ft.	24.4m
4502-16	Pure Copper	16	.051"	1.3mm	1 lb.	454g	Spool	126 ft.	38.4m
4502-20	Pure Copper	20	.032"	0.8mm	1 lb.	454g	Spool	315 ft.	96m
4503-14	Pure Copper	14	.064"	1.6mm	4 oz.	113g	Spool	20 ft.	6m
4503-16	Pure Copper	16	.051"	1.3mm	4 oz.	113g	Spool	32 ft.	9.8m
4503-20	Pure Copper	20	.032"	0.8mm	4 oz.	113g	Spool	79 ft.	24m
4501	Brass	16	.051"	1.3mm	-----	-----	Roll	27 ft.	8.2m
45001	Brass	20	.032"	.8mm	-----	-----	Roll	50 ft.	15.2m
4520-14	Tinned Copper	14	.064"	1.6mm	4 oz.	113g	Spool	20 ft.	6m
4520-16	Tinned Copper	16	.051"	1.3mm	4 oz.	113g	Spool	32 ft.	9.8m
4520-18	Tinned Copper	18	.040"	1.0mm	4 oz.	113g	Spool	50 ft.	15.2m
4520-20	Tinned Copper	20	.032"	0.8mm	4 oz.	113g	Spool	79 ft.	24m
4521-14	Tinned Copper	14	.064"	1.6mm	1 lb.	454g	Spool	80 ft.	24.4m
4521-16	Tinned Copper	16	.051"	1.3mm	1 lb.	454g	Spool	128 ft.	39.0m
4521-18	Tinned Copper	18	.040"	1.0mm	1 lb.	454g	Spool	203 ft.	61.9m
4521-20	Tinned Copper	20	.032"	0.8mm	1 lb.	454g	Spool	323 ft.	98.5m
4525	Braided Tinned Copper		.125"	3.2mm	-----	-----	Roll	100 ft.	30.5m
450417	High Temp Wire	17	.045"	1.1mm	-----	-----	Roll	10 ft.	3m
450424	High Temp Wire	24	.020"	.5mm	-----	-----	Roll	10 ft.	3m
45261	Twisted Tinned Copper	20	.032"	0.8mm	2-3/4 oz.	78g	Roll	25 ft.	7.6m
45262	Twisted Tinned Copper	20	.032"	0.8mm	11 oz.	312g	Roll	100 ft.	30.5m
45263	Twisted Tinned Copper	14	.064"	1.6mm	11 oz.	312g	Roll	25 ft.	7.6m
45264	Twisted Tinned Copper	14	.064"	1.6mm	2-3/4 oz.	78g	Roll	100 ft.	30.5m
45280	Twisted Bright Brass	20	.032"	0.8mm	2-3/4 oz.	78g	Coil	24 ft.	7.3m

\*Dimensions and weights are approximate.